

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : AXIAL PRO
Design code : A21796A
Product Registration Number : PCS 06258

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Herbicide

1.3 Details of the supplier of the safety data sheet

Company : Syngenta Ireland Limited
Block 6 Cleaboy Business Park, Old Kilmeaden Road,
Waterford
Ireland
Telephone : (051) 377203
Telefax : (051) 354748
E-mail address of person responsible for the SDS : cropsales.ie@syngenta.com

1.4 Emergency telephone number

Emergency telephone number : +44 1484 538444

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Skin sensitisation, Sub-category 1A	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H361d Suspected of damaging the unborn child.
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains pinoxaden. May produce an allergic reaction.
EUH208 Contains cloquintocet-mexyl. May produce an allergic reaction.
EUH401 To avoid risks to human health and the environment, comply with the instructions for use.
SP 1 Do not contaminate water with the product or its container (Do not clean application equipment near surface water/Avoid contamination via drains from farmyards and roads).

Precautionary statements : P102 Keep out of reach of children.
P202 Do not handle until all safety precautions have been read and understood.

Prevention:

P261 Avoid breathing vapours.
P261 Avoid breathing spray.
P280 Wear protective gloves/ protective clothing.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P391 Collect spillage.

Disposal:

P501 Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty triple rinsed clean containers which can be disposed of as non-hazardous waste.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL PRO

Version
6.0

Revision Date:
05.01.2021

SDS Number:
S00048150959

This version replaces all previous versions.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified	64742-94-5 265-198-5 649-424-00-3 01-2119451151-53, 01-2119451097-39	Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 25 - < 30
2-methylpentane-2,4-diol	107-41-5 203-489-0 603-053-00-3 01-2119539582-35	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 10 - < 20
pinoxaden (ISO)	243973-20-8 607-726-00-2	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1A; H317 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) Aquatic Acute 1; H400 Aquatic Chronic 3; H412 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 3 - < 10
cloquintocet-mexyl	99607-70-2 01-2119381871-32, 01-2119387592-28	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT RE 2; H373 (Urinary system, Liver) Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 1 - < 2.5
naphthalene	91-20-3 202-049-5	Flam. Sol. 2; H228 Acute Tox. 4; H302	>= 0.25 - < 1

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

	601-052-00-2	Carc. 2; H351 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	
--	--------------	---	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Have the product container, label or Safety Data Sheet with you when calling the emergency number, a poison control center or physician, or going for treatment.
- If inhaled : Move the victim to fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Keep patient warm and at rest.
Call a physician or poison control centre immediately.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with plenty of water.
If skin irritation persists, call a physician.
Wash contaminated clothing before re-use.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Remove contact lenses.
Immediate medical attention is required.
- If swallowed : If swallowed, seek medical advice immediately and show this container or label.
Do not induce vomiting: contains petroleum distillates and/or aromatic solvents.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : There is no specific antidote available.
Treat symptomatically.
Do not induce vomiting: contains petroleum distillates and/or aromatic solvents.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Extinguishing media - small fires
Use water spray, alcohol-resistant foam, dry chemical or

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

carbon dioxide.
Extinguishing media - large fires
Alcohol-resistant foam
or
Water spray

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear full protective clothing and self-contained breathing apparatus.

Further information : Do not allow run-off from fire fighting to enter drains or water courses.
Cool closed containers exposed to fire with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Clean contaminated surface thoroughly.
Clean with detergents. Avoid solvents.
Retain and dispose of contaminated wash water.

6.4 Reference to other sections

For disposal considerations see section 13., Refer to protective measures listed in sections 7 and 8.

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : No special protective measures against fire required.
Avoid contact with skin and eyes.
When using do not eat, drink or smoke.
For personal protection see section 8.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No special storage conditions required. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

Specific use(s) : For proper and safe use of this product, please refer to the approval conditions laid down on the product label.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified	64742-94-5	TWA	8 ppm 50 mg/m ³	Supplier
2-methylpentane-2,4-diol	107-41-5	OELV - 15 min (STEL)	25 ppm 125 mg/m ³	IE OEL
pinoxaden (ISO)	243973-20-8	TLV-C	0.1 mg/m ³	Syngenta
cloquintocet-mexyl	99607-70-2	TWA	5 mg/m ³	Syngenta
naphthalene	91-20-3	TWA	10 ppm 50 mg/m ³	91/322/EEC
	Further information: Indicative			
	91-20-3	OELV - 8 hrs (TWA)	10 ppm 50 mg/m ³	IE OEL

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
tris(2-ethylhexyl) phosphate	Workers	Inhalation	Long-term systemic effects	350 mg/m ³
	Workers	Inhalation	Acute systemic effects	2800 mg/m ³
	Workers	Dermal	Long-term systemic effects	50 mg/kg
	Workers	Dermal	Acute systemic	40 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL PRO

Version
6.0

Revision Date:
05.01.2021

SDS Number:
S00048150959

This version replaces all previous versions.

			effects	
	Consumers	Dermal	Acute systemic effects	200 mg/kg
	Consumers	Dermal	Long-term systemic effects	25 mg/kg
	Consumers	Inhalation	Acute systemic effects	500 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	62.5 mg/m ³
	Consumers	Oral	Acute systemic effects	200 mg/kg
	Consumers	Oral	Long-term systemic effects	25 mg/kg
2-methylpentane-2,4-diol	Workers	Inhalation	Short-term exposure, Local effects	98 mg/m ³
	Workers	Inhalation	Long-term systemic effects	14 mg/m ³
	Workers	Inhalation	Long-term local effects	49 mg/m ³
	Workers	Dermal	Long-term systemic effects	2 mg/kg
	Consumers	Inhalation	Short-term exposure, Local effects	49 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	3.5 mg/m ³
	Consumers	Inhalation	Long-term local effects	25 mg/m ³
	Consumers	Oral	Long-term systemic effects	1 mg/kg
	Consumers	Dermal	Long-term systemic effects	1 mg/kg
Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified	Workers	Dermal	Long-term systemic effects	12.5 mg/kg
	Workers	Inhalation	Long-term systemic effects	150 mg/m ³
	Consumers	Dermal	Long-term systemic effects	7.5 mg/kg
	Consumers	Inhalation	Long-term systemic effects	32 mg/m ³
	Consumers	Oral	Long-term systemic effects	7.5 mg/kg
cloquintocet-mexyl	Industrial use	Dermal	Long-term exposure, Systemic effects	3.33 mg/kg
	Industrial use	Inhalation	Long-term exposure, Systemic effects	0.303 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
tris(2-ethylhexyl) phosphate	Sewage treatment plant	1 mg/l
2-methylpentane-2,4-diol	Fresh water	0.429 mg/l
	Marine water	0.0429 mg/l

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

	Fresh water sediment	1.79 mg/kg
	Marine sediment	0.179 mg/kg
	Soil	0.11 mg/kg
cloquintocet-mexyl	Fresh water	0.0018 mg/l
	Fresh water sediment	0.934 mg/kg dry weight (d.w.)
	Marine water	0.00018 mg/l
	Marine sediment	0.0934 mg/kg dry weight (d.w.)
	Soil	0.463 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Containment and/or segregation is the most reliable technical protection measure if exposure cannot be eliminated.

The extent of these protection measures depends on the actual risks in use.

Maintain air concentrations below occupational exposure standards.
Where necessary, seek additional occupational hygiene advice.

Personal protective equipment

Eye protection : No special protective equipment required.
Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : 0.5 mm

Remarks : Wear protective gloves. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection : The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Remove and wash contaminated clothing before re-use.
Wear as appropriate:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

- Respiratory protection : Impervious clothing
: No personal respiratory protective equipment normally required.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
- Protective measures : The use of technical measures should always have priority over the use of personal protective equipment.
When selecting personal protective equipment, seek appropriate professional advice.
-

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : clear to opalescent
Colour : light yellow
- Odour : aromatic
Odour Threshold : No data available
- pH : 3 - 7
Concentration: 1 % w/v
- Melting point/range : No data available
- Boiling point/boiling range : No data available
- Flash point : 104 °C
Method: Pensky-Martens closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available
- Density : 0.95 - 0.99 g/cm³ (20 °C)
- Solubility(ies)
Water solubility : No data available
Solubility in other solvents : No data available
- Partition coefficient: n-octanol/water : No data available

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

Auto-ignition temperature : 370 °C

Decomposition temperature : No data available

Viscosity

 Viscosity, dynamic : No data available

 Viscosity, kinematic : 22.7 ymm²/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Ingestion
Inhalation
Skin contact
Eye contact

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

Acute toxicity

Product:

- Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials
- Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method
- Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Components:

2-methylpentane-2,4-diol:

- Acute oral toxicity : LD50 Oral (Rat): 2,000 mg/kg
- Acute dermal toxicity : LD50 Dermal (Rat): 2,000 mg/kg

pinoxaden (ISO):

- Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
- Acute inhalation toxicity : LC50 (Rat, male): 4.63 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute toxicity estimate: 4.63 mg/l
Test atmosphere: dust/mist
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
- Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

cloquintocet-mexyl:

- Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat, male and female): > 0.935 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The component/mixture is moderately toxic after short term inhalation.
Remarks: Highest attainable concentration

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

naphthalene:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Skin corrosion/irritation

Product:

Species : Rabbit
Result : Irritating to skin.
Remarks : Based on data from similar materials

Components:

2-methylpentane-2,4-diol:

Species : Rabbit
Result : Irritating to skin.

pinoxaden (ISO):

Method : Based on Human Evidence
Result : Irritating to skin.

cloquintocet-mexyl:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Product:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Components:

2-methylpentane-2,4-diol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

pinoxaden (ISO):

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

cloquintocet-mexyl:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitisation

Product:

Test Type : Buehler Test
Species : Guinea pig
Result : The product is a skin sensitiser, sub-category 1A.
Remarks : Based on data from similar materials

Components:

pinoxaden (ISO):

Test Type : mouse lymphoma cells
Species : Mouse
Result : The product is a skin sensitiser, sub-category 1A.

Test Type : Respiratory sensitisation
Result : Does not cause respiratory sensitisation.
Remarks : Experience with human exposure

cloquintocet-mexyl:

Species : Guinea pig
Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Components:

2-methylpentane-2,4-diol:

Germ cell mutagenicity-Assessment : In vitro tests did not show mutagenic effects

pinoxaden (ISO):

Germ cell mutagenicity-Assessment : Animal testing did not show any mutagenic effects.

cloquintocet-mexyl:

Germ cell mutagenicity-Assessment : Animal testing did not show any mutagenic effects.

Carcinogenicity

Components:

2-methylpentane-2,4-diol:

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

pinoxaden (ISO):

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

cloquintocet-mexyl:

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

naphthalene:

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Components:

2-methylpentane-2,4-diol:

Reproductive toxicity - Assessment : No toxicity to reproduction

pinoxaden (ISO):

Reproductive toxicity - Assessment : No toxicity to reproduction

cloquintocet-mexyl:

Reproductive toxicity - Assessment : No toxicity to reproduction

STOT - single exposure

Components:

pinoxaden (ISO):

Assessment : Based on Human Evidence, The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

Remarks : Breathing difficulties
Cough
Acute irritation of the respiratory system leading to tightness of the chest and an asthmatic condition.

cloquintocet-mexyl:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Components:

pinoxaden (ISO):

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

cloquintocet-mexyl:

Target Organs : Urinary system, Liver
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 19 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 32 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

NOEC (Raphidocelis subcapitata (freshwater green alga)): 5.5 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

pinoxaden (ISO):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 10.3 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 52 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 41 mg/l

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

Exposure time: 72 h

ErC50 (Skeletonema costatum (marine diatom)): 1.72 mg/l
Exposure time: 72 h

NOEC (Skeletonema costatum (marine diatom)): 0.94 mg/l
End point: Growth rate
Exposure time: 96 h

NOEC (Lemna gibba (gibbous duckweed)): 0.73 mg/l
End point: Growth rate
Exposure time: 7 d

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC: 6.6 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)

M-Factor (Chronic aquatic toxicity) : 1

cloquintocet-mexyl:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.97 mg/l
Exposure time: 96 h

LC50 (Gobiocypris rarus (rare gudgeon)): 0.102 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0.82 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 2.2 mg/l
Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 0.12 mg/l
End point: Growth rate
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 0.437 mg/l
Exposure time: 21 d
Species: Daphnia (water flea)

M-Factor (Chronic aquatic toxicity) : 1

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

naphthalene:

Ecotoxicology Assessment

- Acute aquatic toxicity : Very toxic to aquatic life.
Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

2-methylpentane-2,4-diol:

Biodegradability : Result: Readily biodegradable.

pinoxaden (ISO):

Biodegradability : Result: rapidly degradable
Stability in water : Degradation half life: 0.3 d
Remarks: Product is not persistent.

cloquintocet-mexyl:

Biodegradability : Result: Not readily biodegradable.
Stability in water : Degradation half life: 0.4 d
Remarks: Product is not persistent.

12.3 Bioaccumulative potential

Components:

pinoxaden (ISO):

Bioaccumulation : Remarks: Low bioaccumulation potential.

cloquintocet-mexyl:

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 5.24 (25 °C)

12.4 Mobility in soil

Components:

pinoxaden (ISO):

Distribution among environmental compartments : Remarks: Moderately mobile in soils
Stability in soil : Dissipation time: 0.1 - 1.8 d
Percentage dissipation: 50 % (DT50)
Remarks: Product is not persistent.

cloquintocet-mexyl:

Distribution among : Remarks: immobile

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

environmental compartments
Stability in soil : Dissipation time: 2.4 d
Percentage dissipation: 50 % (DT50)
Remarks: Product is not persistent.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Components:

2-methylpentane-2,4-diol:

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).. This substance is not considered to be very persistent and very bioaccumulating (vPvB)..

pinoxaden (ISO):

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).. This substance is not considered to be very persistent and very bioaccumulating (vPvB)..

cloquintocet-mexyl:

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).. This substance is not considered to be very persistent and very bioaccumulating (vPvB)..

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not dispose of waste into sewer.
Where possible recycling is preferred to disposal or incineration.
If recycling is not practicable, dispose of in compliance with local regulations.

Contaminated packaging : Empty remaining contents.
Triple rinse containers.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

Do not re-use empty containers.

Waste Code : uncleaned packagings
15 01 10, packaging containing residues of or contaminated
by hazardous substances

SECTION 14: Transport information

14.1 UN number

ADN : UN 3082
ADR : UN 3082
RID : UN 3082
IMDG : UN 3082
IATA : UN 3082

14.2 UN proper shipping name

ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(CLOQUINTOCET-MEXYL AND SOLVENT NAPHTHA)
ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(CLOQUINTOCET-MEXYL AND SOLVENT NAPHTHA)
RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(CLOQUINTOCET-MEXYL AND SOLVENT NAPHTHA)
IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(CLOQUINTOCET-MEXYL AND SOLVENT NAPHTHA)
IATA : Environmentally hazardous substance, liquid, n.o.s.
(CLOQUINTOCET-MEXYL AND SOLVENT NAPHTHA)

14.3 Transport hazard class(es)

ADN : 9
ADR : 9
RID : 9
IMDG : 9
IATA : 9

14.4 Packing group

ADN
Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3
- REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable
- REACH - List of substances subject to authorisation (Annex XIV) : Not applicable
- Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
- Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable
- Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable
- Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
E2	ENVIRONMENTAL HAZARDS	200 t	500 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2,500 t	25,000 t

Other regulations:

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.
Use plant protection products safely. Always read the label and product information before use.
Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.
Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance when it is used in the specified applications.

SECTION 16: Other information

Full text of H-Statements

H228	: Flammable solid.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H351	: Suspected of causing cancer.
H361d	: Suspected of damaging the unborn child.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Irrit.	: Eye irritation
Flam. Sol.	: Flammable solids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
91/322/EEC	: Europe. Commission Directive 91/322/EEC on establishing indicative limit values
IE OEL	: Ireland. List of Chemical Agents and Occupational Exposure Limit Values - Schedule 1
91/322/EEC / TWA	: Limit Value - eight hours
IE OEL / OELV - 8 hrs (TWA)	: Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL)	: Occupational exposure limit value (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL PRO

Version 6.0 Revision Date: 05.01.2021 SDS Number: S00048150959 This version replaces all previous versions.

List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Skin Irrit. 2 H315

Skin Sens. 1A H317

Repr. 2 H361d

Aquatic Chronic 2 H411

Classification procedure:

Based on product data or assessment

Based on product data or assessment

Calculation method

Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IE / EN